

0W20

FLAGSHIP DRACO

FULLY SYNTHETIC

High performance 100% synthetic "Fuel Economy" lubricant, specially designed for hybrid electric vehicles (H.E.V.) and rechargeable hybrids (P.H.E.V.) equipped with recent petrol engines, turbo or naturally aspirated, direct or indirect injection. It is also recommended for battery electric vehicles (B.E.V.) equipped with a petrol engine to extend the range (Range Extender).

QUALITY LEVEL: API SN | ACEA A3 / B4 | ILSAC GF-5 |
Ford WSS-M2C930-A | Chrysler MS-6395 | Honda | Nissan

SAFETY & HEALTH

Security data sheet are available upon request and should be consulted for more appropriate information. The company shall not be liable for any damages caused by misuse, or if precautions are not taken.

TECHNICAL PROPERTIES

Specification (SAE 0W20) API SN

Test Description	Unit	Test Method	Results
Density @15.6°C	g/ml	ASTM-1298	0,846
Kinematic Viscosity @ 40°C	mm2/S	ASTM-445	37/38
Kinematic Viscosity @ 100°C	mm2/S	ASTM-445	6,1/9,3
Viscosity index (VI)	ASTM-2270	>150
Flash Point, Cleveland open cup	°C	ASTM D-92	>225
Pour Point	°C	ASTM D-97	<-41
Total Base Number	mgKOH/g	ASTM D-2896	>9,0
Sulphated Ash	Mass%	ASTM D-874	<0,8

The information above is based on current production data and can vary within given tolerances. Temperature range is given as a guideline only. Information and data can be changed without previous notification. This information replaces prior editions.

