

# 5W30

# FLAGSHIP C2

## FULLY SYNTHETIC

A universal multigrade engine oil developed according to the latest technical advances engine oil, based on synthetic technology. Carefully selected, highly effective additives give this high-performance engine oil the following outstanding

properties:

- Very good cold start properties
- A reliable lubricating film at high operating temperatures
- Very good detergent and dispersant properties
- Very good protection against wear, corrosion and foaming

**QUALITY LEVEL: API SN ACEA C2/C3**

**VW 505.01|BMW Long Life-04|MB 229.51 / 229.52**

**GM Dexos 2| Opel OV 040 1547 – D30**

## SAFETY & HEALTH

Security data sheet are available upon request and should be consulted for more appropriate information. The company shall not be liable for any damages caused by misuse, or if precautions are not taken.

## TECHNICAL PROPERTIES

### Specification (SAE 5W30 C2) API SN

Test Description	Unit	Test Method	Results
Density @15.6°C	g/ml	ASTM-1298	0855
Kinematic Viscosity @ 40°C	mm2/S	ASTM-445	73
Kinematic Viscosity @ 100°C	mm2/S	ASTM-445	12,1
Viscosity index (VI)	.....	ASTM-2270	>163
Flash Point, Cleveland open cup	°C	ASTM D-92	>230
Pour Point	°C	ASTM D-97	<-36
Total Base Number	mgKOH/g	ASTM D-2896	>7,8
Sulphated Ash	Mass%	ASTM D-874	<0,77

The information above is based on current production data and can vary within given tolerances. Temperature range is given as a guideline only. Information and data can be changed without previous notification. This information replaces prior editions.

