

5W30 LL

FLAGSHIP C3

FULLY SYNTHETIC

Fully synthetic lubricant formulated with PAO and Group III synthetic base oils, with specific additives of last generation to meet the most demanding standards presented, suitable for use in modern gasoline and diesel VAG group. It is suitable to meet the new specifications for VW 504.00/507.00 VW AG with pump injector system which require low viscosity lubricants and "Mid SAPS". It is suitable for cars equipped with a diesel particle filter (DPF).

QUALITY LEVEL: API SN / CF ACEA C2/C3

VW 504.00 / 507.00 | BMW Long Life-04 | Porsche C30 | MB 229.52

PSA B712290 | GM OPEL Dexos 2 | Fiat 9.5553-DS1 | Fiat 9.55535-GS1

SAFETY & HEALTH

Security data sheet are available upon request and should be consulted for more appropriate information. The company shall not be liable for any damages caused by misuse, or if precautions are not taken.

TECHNICAL PROPERTIES

Specification (SAE 5W30 LL C3) API SN/CF

Test Description	Unit	Test Method	Results
Density @15.6°C	g/ml	ASTM-1298	0,849/0855
Kinematic Viscosity @ 40°C	mm2/S	ASTM-445	64/70
Kinematic Viscosity @ 100°C	mm2/S	ASTM-445	9,8/12
Viscosity index (VI)	ASTM-2270	>165
Flash Point, Cleveland open cup	°C	ASTM D-92	>225
Pour Point	°C	ASTM D-97	<-40
Total Base Number	mgKOH/g	ASTM D-2896	>8,0
Sulphated Ash	Mass%	ASTM D-874	<0,8

The information above is based on current production data and can vary within given tolerances. Temperature range is given as a guideline only. Information and data can be changed without previous notification. This information replaces prior editions.

