

Antifreeze GW 12 KONZENTRAT

Long-term radiator protection for all cars

B7 Antifreeze GW 12 concentrate is an ethylene glycol based coolant for all motor vehicles for which silicate-free products are prescribed (eg Ford, GM and MAN). It is suitable for all common engines up to modern high-performance aluminum engines. It is compatible with all products of the brand (also VW G 11).

B7 Antifreeze GW 12 concentrate is suitable as a permanent filler for cast iron and aluminum engines, protects all metallic materials in the system, is environmentally friendly as it is free of nitrite, amine, phosphate and silicate and provides year round protection for the refrigeration system.

QUALITY LEVEL

- VW/Audi/Seat/Skoda TL774-D/F (G12/12+)
- MB 325.3
- ADE
- Bergen Engines 2.13.01
- DAF 74002 A
- Aston Martin
- Case New Holland MAT3624
- Detroit DFS93K217
- Behr
- Caterpillar A4.05.09.01
- Deutz DQC CB-14
- Chevrolet
- Cummins CES 14603/CES 14439
- Fiat MAT3624
- Claas
- Cummins IS series u N14
- Ford WSS-M97B44-D
- Fendt
- Deutz/MWM 0199-99-2091/8
- Foton Q-FPT 2313005-2013
- Great Wall
- Saturn
- Jaguar STJLR 651.5003
- Jaguar CMR 8229
- Hitachi
- John Deere JDM H5
- Jenbacher TA 1000-0201
- Isuzu
- Komatsu 07.892 (2009)
- Liebherr MD1-36-130
- Karosa
- Land-Rover STJLR 651.5003
- MAK A4.05.09.01
- Kobelco
- Leyland Trucks DW03245403
- MAN 324 SNF
- Proton
- Mack 014 GS 17009
- MAN B&W AG D36 5600
- Rover
- Opel-GM GMW 3420
- Mazda MEZ MN 121 D
- Santana Motors
- Renault Trucks 41-01-001/-S Type D
- Mitsubishi MHI

The information above is based on current production data and can vary within given tolerances. Temperature range is given as a guideline only. Information and data can be changed without previous notification. This information replaces prior editions.



Antifreeze GW 12 KONZENTRAT

- SACM Diesel DLP799861
- MTU MTL 5048
- Semt Pielstick
- Vauxhall GM 6277M (+B040 1065)
- Saab B 040 1065
- Tedom
- Vauxhall GME L1301
- Skoda 61-0-0257
- Thermo King
- Volvo 014 GS 17009
- Wärtsilä 32-9011 Valtra
- E/L-1415b (MIL-Italy)
- ASTM D4656
- FVV Heft R443 (Germany)
- FSD 8704 (MIL-Sweden)
- ASTM D4985
- JASO M325
- NATO S-759
- ASTM D6210
- KSM 2142
- Önorm V5123
- BR 637
- Volvo
- Penta/Trucks/Construction
- Waukesha
- Yanmar
- BT-PS-606 A (MIL-Belgium)
- SAE J1034
- BS 6580
- DCSEA 615/C (MIL-France)
- UNE 26-361-88/1
- ASTM D3306
- NFR 15-601

Mixture table	Frost Protection up to	-19°C	-24°C	-35°C	-37°C
Antifreeze GW 12	Vol %	30	40	45	50
Tap watter	Vol %	70	60	55	50

SAFETY & HEALTH

Security data sheet are available upon request and should be consulted for more appropriate information. The company shall not be liable for any damages caused by misuse, or if precautions are not taken.

TECHNICAL PROPERTIES

Specification (Antifreeze GW12) Konzentrat

Test Description	Unit	Results
Density @20°C	Kg/m3	1112
Colour		Violet
Flash Point, Cleveland open cup	°C	>100
Boiling Point	°C	>170
pH value (35% strength)		8,3

The information above is based on current production data and can vary within given tolerances. Temperature range is given as a guideline only. Information and data can be changed without previous notification. This information replaces prior editions.

