

0W30 B7 Premium C3

B7 Premium C3 SAE 0W-30 wurde gezielt für die Verwendung bei Diesel- und Benzinmotoren von Personenkraftwagen der BMW Gruppe entwickelt. Es kann auch bei anderen OEM-Diesel- und Benzinmotoren verwendet werden, bei denen ein 0W30-Grade Low SAPS-Öl benötigt wird.

B7 Premium C3 SAE 0W-30 is aimed and specially formulated for usage in diesel and gasoline engines of BMW group passenger vehicles. It can also be used in other OEM diesel and gasoline engines where there is a need for a 0W30 grade low SAPS oil.

EIGENSCHAFTEN/ PROPERTIES:

Lange Ölwechselintervalle

Long Service Intervall

Geringe Emissionen (CO₂)

Low Emission (CO₂)

Kraftstoffeinsparung

Fuel Economy (FE)

Low SAPS (niedrigem Gehalt an Sulfatasche, Phosphor und Schwefel)

Low SAPS (low Content Sulphated-Ash, Phosphorus and Sulphur)

SPEZIFIKATIONEN/ SPECIFICATIONS:

API SN/CF | ACEA C3

**BMW LONGLIFE-04 | FIAT 9.55535-DS1 | FIAT 9.55535-GS1
MB 229.51**

SAFETY & HEALTH

Security data sheet are available upon request and should be consulted for more appropriate information. The company shall not be liable for any damages caused by misuse, or if precautions are not taken.



0W30 B7 Premium C3

TECHNISCHE DATEN / TECHNICAL CHARACTERISTICS:

0W30 B7 Premium C3 API C3

Test Description	Unit	Test Method	Results
Density @15.6°C	g/ml	ASTM-1298	0,842
Kinematic Viscosity @ 40°C	mm2/S	ASTM-445	66,6
Kinematic Viscosity @ 100°C	mm2/S	ASTM-445	12,1
Viscosity index (VI)		ASTM-2270	182
Flash Point, Cleveland open cup	°C	ASTM D-92	>225
Sulphated Ash	Mass %	ASTM D874	0,8
Pour Point	°C	ASTM D-97	<-54
Total Base Number	mgKOH/g	ASTM D-2896	>7,8

The information above is based on current production data and can vary within given tolerances. Temperature range is given as a guideline only. Information and data can be changed without previous notification. This information replaces prior editions.

