

5W20 B7 FLAGSHIP D1-3

B7 Flagship D1-3 SAE 5W20 wurde speziell entwickelt, um die anspruchsvollen Anforderungen der neuesten GM Dexos1TM Gen3-Spezifikation und ILSAC zu erfüllen. Insbesondere für die ILSAC GF-6-Standards, bei denen Kraftstoffeinsparung und CO₂-Reduzierung wichtig sind. **B7 Flagship D1-3 SAE 5W20** garantiert die Leistung, welche für die neuesten Anforderungen für benzinbetriebene Pkw in den USA und Asien benötigt wird. Weiterhin ist es für Hybridautos geeignet, wenn die OEM-Spezifikationen erfüllt sind.

B7 Flagship D1-3 SAE 5W20 has been specially developed to meet the demanding requirements of the latest GM Dexos1TM Gen3 specification and ILSAC. Especially for the ILSAC GF-6 standards where fuel economy and CO₂ reduction are important. **B7 Flagship D1-3 SAE 5W20** guarantees the performance for the latest requirements for gasoline passenger cars in the USA and Asia. It is also suitable for hybrid

EIGENSCHAFTEN/ PROPERTIES:

- LSPI-Schutz und -Verbesserung für T/GDI-Fahrzeuge
- Verschleißvermeidung an der Nockenwelle
- Kettenverschleißschutz vor Rußpartikeln in GDI-Motoren
- LSPI Protection and improvement for T/GDI vehicles
- Avoid Wear on the Camshaft
- Chain-wear-protection against Soot-Particles in GDI-engines

SPEZIFIKATIONEN/ SPECIFICATIONS:

API SN | SN PLUS | SN/RC | SP/RC

CHEVROLET SFU | CHRYSLER SFU | FIAT SFU | FORD WSS-M2C947-A | GM 6094M | HYUNDAI SFU
LEXUS SFU | MITSUBISHI SFU | TIANJIN SFU | CHRYSLER MS 6395 | CHRYSLER MS 10797 | KIA SFU
DODGE SFU | FIAT 9.55535-CR1 | FORD WSS-M2C945-A | FORD WSS-M2C946-A | TOYOTA SFU
FORD WSS-M2C962-A | GM dexos1 Gen 3 | ILSAC GF-6 A | ILSAC GF-5 | LANCIA SFU | LINCOLN SFU
MAZDA SFU | SCION SFU | SSANGYONG SFU



5W20 B7 FLAGSHIP D1-3

TECHNISCHE DATEN / TECHNICAL CHARACTERISTICS:

5W20 B7 Flagship D1-3 API SP|SP/RC|SN Plus|SN/RC

Eigenschaften/Properties	Einheit/Unit	Test	Wert/Value
Density @15.6°C	g/ml	ASTM D4052	0,848
Kinematic Viscosity @ 40°C	mm ² /S	ASTM D445	45,1
Kinematic Viscosity @ 100°C	mm ² /S	ASTM D445	8,6
Viscosity index (VI)		ASTM D2270	172
Flash Point, Cleveland open cup	°C	ASTM D92	225
Pour Point	°C	ASTM D97	-33
Total Base Number	mgKOH/g	ASTM D2896	7,4
Sulphated Ash	Mass%	ASTM D874	0,79

The information above is based on current production data and can vary within given tolerances. Temperature range is given as a guideline only. Information and data can be changed without previous notification. This information replaces prior editions.

SAFETY & HEALTH

Security data sheet are available upon request and should be consulted for more appropriate information. The company shall not be liable for any damages caused by misuse, or if precautions are not taken.

