

5W30 B7 Flagship C2

B7 Flagship C2 SAE 5W-30 Ein universelles Mehrbereichs-Motoröl, das nach den neuesten technischen Erkenntnissen entwickelt wurde und auf synthetischer Technologie basiert. Sorgfältig ausgewählte, hochwirksame Additive verleihen diesem Öl spezifische Eigenschaften für Hochleistungsmotoren. **B7 Flagship C2 SAE 5W-30** wurde entwickelt, um die Spezifikationen VW 504.00 und 507.00 zu erfüllen, und kann in verschiedenen EURO 4- und EURO 5-Motoren mit Dieselpartikelfiltern gewartet werden.

B7 Flagship C2 SAE 5W-30 A universal multigrade engine oil developed according to the latest technical findings and based on synthetic technology. Carefully selected, highly effective additives give this oil specific properties for high-performance engines. **B7 Flagship C2 SAE 5W-30** has been developed to meet the specifications VW 504.00 and 507.00 and can be used in various EURO 4 and EURO 5 engines with diesel particulate filters.

EIGENSCHAFTEN/ PROPERTIES:

- Rundumschutz des Abgasnachbehandlungssystems
- Lange Ölwechselintervalle
- Mid-SAPS Motorenöl (Mittlerer Gehalt an Sulfatasche, Phosphor und Schwefel)
- Erfüllt alle Motorschutzanforderungen der Klassifikation ACEA C2
- Full Aftertreatment System Protection
- Long Service Interval
- Mid-SAPS Engine Oil (Medium Content Sulphated-Ash, Phosphorus and Sulphur)
- Meets all Engine Protection Requirements of ACEA C2

SPEZIFIKATIONEN/ SPECIFICATIONS:

API SN/CF | ACEA C2

BMW LONGLIFE-04 | MB 229.51 | MB 229.52 | PORSCHE C30 | VW 504 00 | VW 507 00
GM DEXOS 2 | OPEL OV 040 157 | PSA B71 2290



5W30 B7 Flagship C2

TECHNISCHE DATEN / TECHNICAL CHARACTERISTICS:

5W20 B7 Flagship C2 API SN/CF ACEA C2

Test Description	Unit	Test Method	Results
Density @15.6°C	g/ml	ASTM-1298	0,854
Kinematic Viscosity @ 40°C	mm2/S	ASTM-445	68
Kinematic Viscosity @ 100°C	mm2/S	ASTM-445	11,7
Viscosity index (VI)		ASTM-2270	169
Flash Point, Cleveland open cup	°C	ASTM D-92	230
Pour Point	°C	ASTM D-97	-33
Sulfated Ash	Mass %	ASTM D874	0,7
Total Base Number	mgKOH/g	ASTM D-2896	8,3

The information above is based on current production data and can vary within given tolerances. Temperature range is given as a guideline only. Information and data can be changed without previous notification. This information replaces prior editions.

SAFETY & HEALTH

Security data sheet are available upon request and should be consulted for more appropriate information. The company shall not be liable for any damages caused by misuse, or if precautions are not taken.

